Custom

Custom

Key	Format	CND	Description
Custom	ans..1024	O	"Custom"-parameter is added to the request data before encryption and is part of encrypted "Data" in request. By this they are protected against manipulation by a consumer. The Custom-value is added to the response in plain text and the "|" is replaced by a "&". By this you can put a single value into Custom-parameter and get multiple key-value-pairs back in response for your own purpose. Please find a samples here: Custom

Sample with multiple custom key-value-pairs

action	request / response	Comments

request / Aufruf	`Custom=Custom1Key=Custom1Val|Custom2Key=Custom2Val|Custom3Key=Custom3Val&`
	`Amount=<amount>&Currency=<currency>&...`
	
	encrypted Request:
	
	`Len=123&Data=A1BA...`
		`Custom1Key=Custom1Val|Custom2Key=Custom2Val|Custom3Key=Custom3Val`
		is considered as **one value** of parameter "Custom"
		
		and is part of Blowfish-encrypted Data

response / Antwort (response =encrypt)	`Len=123&Data=9AF8E997....` `&Custom1Key=Custom1Val&Custom2Key=Custom2Val&Custom3Key=Custom3Val`	You receive Len + Data as encrypted response Custom-value is now part of response in plain text and not encrypted and "|" has been replaced by "&" so you can receive **multiple key-value-pairs**.
response / Antwort (not encrypted)	`mid=YourMerchantId&PayID=a0b2dh1234....` `&Custom1Key=Custom1Val&Custom2Key=Custom2Val&Custom3Key=Custom3Val`	You receive -response unencrypted Custom-value added to response in plain text and "|" has been replaced by "&" so you can receive **multiple key-value-pairs**.

Sample with multiple custom values

action	request / response	Comments

request	`Custom=Custom1Val|Custom2Val|Custom3Val&`
	`Amount=<amount>&Currency=<currency>&...`
	
	encrypted Request:
	
	`Len=123&Data=A1BA...`
		`Custom1Val|Custom2Val|Custom3Val`
		is considered as **one value** of parameter "Custom"
		
		and is part of Blowfish-encrypted Data

response (response=encrypt)	`Len=123&Data=9AF8E997....` `&Custom1Val&Custom2Val&Custom3Val`	You receive Len + Data as encrypted response Custom-value is now part of response in plain text and not encrypted and "|" has been replaced by "&" so you can receive **multiple values**.
response (not encrypted)	`mid=YourMerchantId&PayID=a0b2dh1234....` `&Custom1Val&Custom2Val&Custom3Val`	You receive -response unencrypted Custom-value added to response in plain text and "|" has been replaced by "&" so you can receive **multiple values**.